## **EG05000**

## **Five Channel ECG Module**







## oem.medlab-gmbh.de

- Advanced signal processor technology with digital filtering
- Small size (88 x 53 mm), maximum height 10 mm.
- Monitors I, II, III, aVR, aVL, aVF, C with five lead cable
- · Monitors I, II, III, aVR, aVL, aVF with four lead cable
- · Monitors I, II, III with three lead cable
- · Integrated pacemaker detection and lead-off detection for each electrode
- Measurement of respiration rate over the electrodes (optional)
- Single power supply (5 V DC), 250 mW
- RS232 and TTL level serial asynchronous interface
- Highly accurate isolated ECG Trigger output
- · Integrated patient isolation according to IEC 601-1
- · Integrated defibrillation protection
- Complies with the newest version of IEC 601-2-27
- · Transmission of pulse rate, ECG, and respiration waveform
- Measurement of pulse rate between 30 250 bpm
- · Four amplification stages, four curve transmission speeds
- · ECG cables and adapters available

## Applications:

High-End ECG Monitoring

ECG Triggering for CT scanners, Gamma Cameras aso.





medizinische Diagnosegeräte GmbH

Helmholtzstrasse 1

D 76297 Stutensee near Karlsruhe

Germany

Tel.: +49 (0) 7244 74110 0 FAX: +49(0) 7244 74110 28 sales@medlab-gmbh.de